




8w COB 165 Lumens
 IP65 · Suitable For Wet Locations
 IK08 · Impact Resistant (Vandal Resistant)
 Weight 14.1 lbs



Top View



Mounting Detail

Construction

Aluminum

Less than 0.1% copper content – Marine Grade 6060 extruded & LM6 Aluminum High Pressure die casting provides excellent mechanical strength, clean detailed product lines and excellent heat dissipation.

Pre paint

8 step degrease and phosphate process that includes deoxidizing and etching as well as a zinc and nickel phosphate process before product painting.

Memory Retentive -Silicon Gasket

Provided with special injection molded "fit for purpose" long life high temperature memory retentive silicon gaskets. Maintains the gaskets exact profile and seal over years of use and compression.

Thermal management

LM6 Aluminum is used for its excellent mechanical strength and thermal dissipation properties in low and high ambient temperatures. The superior thermal heat sink design by Ligman used in conjunction with the driver, controls thermals below critical temperature range to ensure maximum luminous flux output, as well as providing long LED service life and ensuring less than 10% lumen depreciation at 50,000 hours.

Surge Suppression

Standard 10kv surge suppressor provided with all fixtures.

BUG Rating

Contact Factory

Finishing

All Ligman products go through an extensive finishing process that includes fettling to improve paint adherence.

Paint

UV Stabilized 4.9Mil thick powder coat paint and baked at 200° C. This process ensures that Ligman products can withstand harsh environments. Rated for use in natatoriums.

MicroPRIM Finishes

MicroPRIM is Ligman's trade marked decorative powder coating technology that permanently infuses colors, patterns, or imagery directly into the surface of luminaires and poles while providing protections that standard powder coating does not offer.

MicroPRIM finishes include nature-inspired wood grains and stone aesthetics, material-inspired finishes such as brushed metal, concrete, and carbon fiber, Solid colors in Ligman standard colors, as well as any RAL or Pantone color, Decorative patterns, custom imagery and more.

Coating and Infusion Process

Metal components are pre-treated and powder coated with a proprietary polyurethane-based coating engineered for outdoor architectural use. Decorative patterns or imagery are then permanently infused into the cured powder coat through a heat-based process, creating a durable, integrated finish.

Performance and Validation

MicroPRIM finishes are suitable for indoor and outdoor applications and meet AAMA2605 architectural coating requirements. Performance is validated through laboratory and real-world testing to ASTM standards for UV exposure, adhesion, abrasion, impact, salt spray, chemical resistance, and graffiti resistance.

All MicroPRIM finishes are backed by Ligman's 10-year warranty.

Key Performance Attributes

- Anti-graffiti resistance
- UV and weather resistance
- Scratch and abrasion resistance
- Natatorium Rated for installation in corrosive environments

Hardware

Provided Hardware is Marine grade 316 Stainless steel.

Anti Seize Screw Holes

Tapped holes are infused with a special anti seize compound designed to prevent seizure of threaded connections, due to electrolysis from heat, corrosive atmospheres and moisture.

Crystal Clear Low Iron Glass Lens

Provided with tempered, impact resistant crystal clear low iron glass ensuring no green glass tinge.

Optics & LED

Precise optic design provides exceptional light control and precise distribution of light.
 LED CRI > 80

Lumen - Maintenance Life

L80 /B10 at 50,000 hours (This means that at least 90% of the LED still achieve 80% of their original flux)

Contemporary urban lighting furniture. Open-sided, three lattice pattern options or your bespoke design.


A stylish Dark Sky Compliant square high performance bollard with downward light distribution using LED lamps. This light column offers optimal visual comfort through glare control by utilizing a controlled optics designed by Ligman. These bollards have a square design providing a unique wide light distribution, offering an architecturally appealing clover leaf pattern on the paving. The internal sides of the supporting pillars are accented by light from the LED.

Color temperature 2700K, 3000K, 3500K and 4000K. The minimalistic shape provides distinctive lighting effects by night and decorative urban effect during the day. Suitable for pedestrian areas, precincts, building surrounds, shopping centers, squares and parks. The Vancouver Bollard comes standard with a unique waterproof internal driver housing compartment that is situated at the top of the pole to stop water and dust from entering the electrical components. This fixture is supplied completely wired with powercord and waterproof gland from the driver enclosure to the base of the column to ensure quick trouble-free installation.

The Vancouver has a specially designed anchor bolt mounting base that is partially buried below ground level to provide a flush fixture finish with the surface, but maintains the rigidity that is required when installing bollards.

Custom bollard heights are available, please specify. Provided with anchor bolts Reduced custom wattages can be provided to suit customer requirements. (Specify total watt requirement per fixture) Designed to complement the Vancouver Light Column UVA-20001

• **NOTE: For the round version of the Vancouver, please see the Benton Light Column and Bollard**



UVA-70041

Vancouver 65 Pillar Light

PROJECT		DATE	
---------	--	------	--

QUANTITY		TYPE		NOTE	
----------	--	------	--	------	--

ORDERING EXAMPLE || UVA - 70041 - 8w - W30 - 02 - 120/277v - Options

UVA-70041				
LAMP	LED COLOR	FINISH COLOR	VOLTAGE	
8w COB 165 Lumens	W27 - 2700K W30 - 3000K W35 - 3500K W40 - 4000K	01 - BLACK RAL 9011 02 - DARK GREY RAL 7043 03 - WHITE RAL 9003 04 - METALLIC SILVER RAL 9006 05 - MATTE SILVER RAL 9006 06 - LIGMAN BRONZE 07 - CUSTOM RAL	120/277v	

--	--	--

ADDITIONAL OPTIONS

- NAT - Natatorium Rated
- HGT - Custom Bollard Height
- GFCI - GFCI Box

- NAT - Natatorium Rated
- DIM - 0-10v Dimming

More Custom Finishes Available Upon Request

Consult factory for pricing and lead times

MicroPRIM FINISHES

-  SW01 - OAK FINISH
-  SW02 - WALNUT FINISH
-  SW03- PINE FINISH
-  DF - DOUGLAS FIR FINISH
-  CW - CHERRY WOOD FINISH
-  NW - NATIONAL WALNUT FINISH
-  SU01 - CONCRETE FINISH
-  SU02 - SOFTSCAPE FINISH
-  SU03 - STONE FINISH
-  SU04 - CORTEN FINISH
-  CSM - Custom Image/Pattern

MicroPRIM FINISHES


-  MP - MAPLE FINISH
-  MHG - MAHOGANY FINISH
-  BH - BEECH FINISH
-  CN - CHESTNUT FINISH
-  WMBL - WHITE MARBLE FINISH
-  MBL - MARBLE FINISH
-  GRNT - GRANITE FINISH
-  BGD - BRUSHED GOLD FINISH
-  BBRZ - BRUSHED BRONZE FINISH
-  CAMO - CAMOUFLAGE FINISH

-  MP01 - MicroPRIM RAL 9011 Black (Glossy)
-  MP02 - MicroPRIM RAL 7043 Dark Grey (Glossy)
-  MP03 - MicroPRIM RAL 9003 White (Glossy)
-  MP04 - MicroPRIM RAL 9006 Metallic Silver (Glossy)
-  MP05 - MicroPRIM RAL 9006 Matte Silver (Matte/Textured)
-  MP06 - MicroPRIM Ligman Bronze (Glossy)
-  MP07 - MicroPRIM Custom Color (Glossy)




MicroPRIM Finish






Vancouver 16

- UVA-20111-33w-1429lm [9.4"x9.4"-13.3"]
- UVA-20112-66w-4287lm [9.4"x9.4"-14.5"]
- UVA-20113-99w-5716lm [9.4"x9.4"-15.7"]
- UVA-20114-132w-7145lm [9.4"x9.4"-17"]




Vancouver 17

- UVA-20121-33w-2858 lm [9.4"x9.4"-13.3"]
- UVA-20122-66w-4287lm [9.4"x9.4"-14.5"]
- UVA-20123-99w-5716lm [9.4"x9.4"-15.7"]
- UVA-20124-132w-7145lm [9.4"x9.4"-17"]




Vancouver 18

- UVA-20131-33w-2858lm [9.4"x9.4"-13.3"]
- UVA-20132-66w-4287lm [9.4"x9.4"-14.5"]
- UVA-20133-99w-5716lm [9.4"x9.4"-15.7"]
- UVA-20134-132w-7145lm [9.4"x9.4"-17"]




Vancouver 19

- UVA-20141-33w-2858lm [9.4"x9.4"-13.3"]
- UVA-20142-66w-4287lm [9.4"x9.4"-14.5"]
- UVA-20143-99w-5716lm [9.4"x9.4"-15.7"]
- UVA-20144-132w-7145lm [9.4"x9.4"-17"]




Vancouver 20

- UVA-20151-33w-1429lm [9.4"x9.4"-12.1"]




Vancouver 21

- UVA-20161-33w-1429lm [9.4"x9.4"-12.1"]



Vancouver 22

- UVA-20171-33w-1429lm [9.4"x9.4"-12.1"]




Vancouver 23

- UVA-20181-33w-1429lm [9.4"x9.4"-12.1"]




Vancouver 24

- UVA-30001-8w-331lm [6.3"x6.3"-15.7"]



Vancouver 25

- UVA-30011-21w-570lm [6.3"x6.3"-23.6"]




Vancouver 26

- UVA-30012-21w-490lm [6.3"x6.3"-23.6"]




Vancouver 27

- UVA-30013-21w-740lm [6.3"x6.3"-23.6"]




Vancouver 28

- UVA-30021-39w-1336lm [9.4"x9.4"-39.3"]
- UVA-30031-33w RGBW-429lm [9.4"x9.4"-39.3"]



Vancouver 29

- UVA-30022-39w-1167lm [9.4"x9.4"-39.3"]
- UVA-30032-33w RGBW-1158lm [9.4"x9.4"-39.3"]



Vancouver 30

- UVA-30023-39w-1670lm [9.4"x9.4"-39.3"]
- UVA-30033-33w RGBW-439lm [9.4"x9.4"-39.3"]



Vancouver 31

· UVA-10101-7w-200lm [4.7" x 4.7" - 23.6"]



Vancouver 33

· UVA-10051-15w-1083lm [6.3" x 6.3" - 39.3"]



Vancouver 34

· UVA-10061-21w-1571lm [9.4" x 9.4" - 39.3"]



Vancouver 35

· UVA-10071-21w-1571lm [9.4" x 9.4" - 39.3"]



Vancouver 36

· UVA-10072-21w-1571lm [9.4" x 9.4" - 39.3"]



Vancouver 37

· UVA-10073-21w-1571lm [9.4" x 9.4" - 39.3"]



Vancouver 38

· UVA-10141-8w-95lm [4.7" x 4.7" - 23.6"]




Vancouver 39

· UVA-10151-15w-418lm [6.3" x 6.3" - 39.3"]




Vancouver 40

· UVA-10161-21w-635lm [9.4" x 9.4" - 39.3"]




Vancouver 41

· UVA-20191-20w-1326lm [6.3" x 6.3" - 9.8"]



Vancouver 42

· UVA-20201-40w-2969 lm [9.4" x 9.4" - 14.7"]



Vancouver 43

· UVA-20211-39/21w-2781/1688lm [9.4"x9.4"-13.3"]



Vancouver 44

· UVA-20212-39/2x21w-2781/2x1688lm [9.4"x9.4"-14.5"]



Vancouver 45

· UVA-20213-39/3x21w-2781/3x1688lm [9.4"x9.4"-15.7"]



Vancouver 46

· UVA-20221-39/21w-4469/1688lm [9.4"x9.4"-13.3"]



Vancouver 47

· UVA-20221-39/2x21w-4469/2x1688lm [9.4"x9.4"-14.5]



Vancouver 48

· UVA-20223-39/3x21w-4469/3x1688lm [9.4"x9.4"-15.7]



Vancouver 49

· UVA-20231-39/21w-2781/1688lm [9.4"x9.4"-13.3]



Vancouver 50

· UVA-20232-39/2x21w-2781/2x1688lm [9.4"x9.4"-14.5]



Vancouver 51

· UVA-20233-39/2x21w-2781/2x1688lm [9.4"x9.4"-15.7]



Vancouver 52

· UVA-20241-40w-2781lm [9.4"x9.4"-12]



Vancouver 53

· UVA-20242-40w-2781lm [9.4"x9.4"-12]



Vancouver 54

· UVA-20243-40w-2781lm [9.4"x9.4"-12]



Vancouver 55

· UVA-20251-21w-710lm [6.3"x6.3"-9.8]



Vancouver 56

· UVA-20261-40w-1485lm [9.4"x9.4"-14.7]



Vancouver 60

· UVA-20281-76w-4140lm [9.4"x9.4"-12]



Vancouver 61

· UVA-20282-76w-4140lm [9.4"x9.4"-12]



Vancouver 62

· UVA-20283-76w-4140lm [9.4"x9.4"-12]



Vancouver 63

· UVA-70021-13w-437lm [6.3"x6.3"-15.7]



Vancouver 64

· UVA-70031-20w-1362lm [9.4"x9.4"-15.7]




Vancouver 65

· UVA-70041-8w-165lm [6.3"x6.3"-15.7"]



Vancouver 66

· UVA-70051-21w-410lm [9.4"x9.4"-15.7"]



Vancouver 67

· UVA-30041-20w-1326lm [6.3"x6.3"-23.6"]




Vancouver 68

· UVA-30042-20w-1326lm [6.3"x6.3"-23.6"]




Vancouver 69

· UVA-30043-20w-1326lm [6.3"x6.3"-23.6"]




Vancouver 70

· UVA-30051-40w-2781lm [9.4"x9.4"-39.3"]



Vancouver 71


· UVA-30052-40w-2781lm [9.4"x9.4"-39.3"]



Vancouver 72

· UVA-30053-40w-2781lm [9.4"x9.4"-39.3"]

Vancouver Product Family



Vancouver 1

- UVA-20001-40w-2969lm [9.4"x9.4"-14.7']



Vancouver 2

- UVA-20011-20w-1414lm [6.3"x6.3"-9.8']




Vancouver 3

- UVA-10001-21w-1270lm [9.4"x9.4"-39.3']




Vancouver 4

- UVA-10011-15w-837lm [6.3"x6.3"-39.3']




Vancouver 5

- UVA-20021-39/21w-1336/1673lm [9.4"x9.4"-13.3']
 - UVA-20022-39/2x21w-1336/2x1673lm [9.4"x9.4"-14.5']
 - UVA-20023-39/3x21w-1336/3x1673lm [9.4"x9.4"-15.7']




Vancouver 6

- UVA-20031-39/21w-1167/1673lm [9.4"x9.4"-13.3']
 - UVA-20032-39/2x21w-1167/2x1673lm [9.4"x9.4"-14.5']
 - UVA-20033-39/3x21w-1167/3x1673lm [9.4"x9.4"-15.7']




Vancouver 7

- UVA-20041-39/21w-1670/1673lm [9.4"x9.4"-13.3']
 - UVA-20042-39/2x21w-1670/2x1673lm [9.4"x9.4"-14.5']
 - UVA-20043-39/3x21w-1670/3x1673lm [9.4"x9.4"-15.7']




Vancouver 8

- UVA-20051-40w-1336lm [9.4"x9.4"-12.1']



Vancouver 9

- UVA-20061-40w-1167lm [9.4"x9.4"-12.1']




Vancouver 10

- UVA-20071-40w-1670lm [9.4"x9.4"-12.1']




Vancouver 11

- UVA-10021-21w-570lm [9.4"x9.4"-39.3']



Vancouver 12

- UVA-10031-21w-490lm [9.4"x9.4"-39.3']



Vancouver 13

- UVA-10041-21w-704lm [9.4"x9.4"-39.3']



Vancouver 14

- UVA-70001-8w-331lm [6.3"x6.3"-15.7']



Vancouver 15

- UVA-70011-21w-815lm [9.4"x9.4"-15.7']